

Free-standing safes

SERIES 3250TK

FREE STANDING SAFES


Feature

Breaking-proof 3D laser cut - Monolithic structure, special steel - Anchoring holes for floor and wall (4+4)
 Special steel bolts, 22 mm diam. - Key extraction impossible with open door - Blue colour, epoxy coating with double phosphating treatment



Pictures shown have only an illustrative purpose, they don't qualify for contractual terms

Technical data



Mod.	Dimensions mm		Bolts	Shelves	Kg
	External	Internal			
	ABC	ABC			
3252TK	370x240x320	330x225x260	2	1	26,5
3254TK	430x290x370	390x275x310	2+2	1	36,8
3255TK	500x330x400	460x315x340	3+2	1	47,7
3257TK	410x570x400	370x555x340	3+2	1	61,6

Locking

Electronic lock

Electronic lock with motorized opening of the bolts
 Proprietary microprocessor
 User code from 6 to 10 digits or letters
 Factory service code
 Non volatile memory to retain the code with drained batteries

12-keys membrane keyboard
Red/green led acoustic and optic feedback signal for code entry, error, low batteries
Powering through 1- 9 volts alkaline battery
External emergency powering through contacts on the keyboard
Motorized grab knob working as advice of door open
Special steel bolts, 22 mm dia